

# WDZX系列 >>> 卧式蒸汽灭菌器

## 产品特点

### PRODUCT FEATURES

#### 实行微电脑智能控制系统:

采用“LED”数显运行工作循环程序, 灭菌结束(报警)后自动停机;

#### 安全联锁装置:

采用电子与机械互动的安全控制结构, 确保锅内有压力时联锁装置自动锁紧锅盖, 避免了误操作或使用不当而产生的不安全因素;

#### 锅盖启闭装置:

采用拨杆式多连杆同步伸缩结构, 使锅盖开启与锁紧安全可靠、灵活轻巧;

#### 预置程序:

可预置固定程序对固体的灭菌;

#### 记忆存储系统:

可存储上次灭菌程序, 便于二次操作;

#### 进水控制:

具有自动进水与补水功能;

#### 排汽控制:

灭菌完成后, 排气阀可按预先设定的灭菌时间倒计时结束后, 数显屏有提示排放蒸汽;

#### 校验接口:

提供温度、压力检验接口, 方便对锅内多点温度进行检测;

#### 操控台动态:

数显屏与指示灯可显示设定的灭菌工作动态与运行的功能提示;

#### 安全配置:

采用电器与机械互动的安全联锁结构, 确保锅内有压力时联锁装置锁住锅盖把手, 避免锅内有压力时开启锅盖。



#### Intelligent microcomputer control system:

Using LED digital control system; After sterilization finished, sterilizer will automatic alarm and shut down.

#### Interlock device:

The control system can real time supervision the sterilizer chamber's temperature and pressure. Only under the safety temperature and pressure can open the sterilizer's cover. Make sure the operator's safety.

#### The structure of cover's opening:

Using 8 rotary extendable stick to improve sealing and safety performance.

#### Preset program:

Can preset fixed program that sterilize solid body.

#### Memory storage system:

Store the last operation program so convenient next operation.

#### Feed water control:

Automatic water intake and water refill function

#### Exhaust steam control :

After sterilization, exhaust steam valve should be opened (Digital display screen reminds exhaust steam) when sterilization time run out.

#### Interface check:

Provide temperature and pressure check interface; convenient to check multiple position temperature measurement.

#### Digital display screen:

Digital display screen and working indicator light display running state.

#### Safety devices:

Adopt the safety interlock structure of electrical and mechanical interaction to ensure that the interlock device locks the lid handle when there is pressure in the pot to avoid opening the lid when there is pressure in the pot.



## HORIZONTAL STEAM STERILIZER



| 型号 | WDZX-200KC | WDZX-300KC |
|----|------------|------------|
| 容积 | 200立升      | 300立升      |

## 技术参数 TECHNICAL PARAMATER

### 参数 / 型号 Parameter/Model

#### 配置 Configuration

#### 材质 Material (mm)

#### 锅体壁厚 Pot wall thickness (mm)

#### 毛重 GW

#### 电压 / 功率 Voltage/Power

#### 包装尺寸 Packing size (mm)

#### 产品尺寸 Product size (mm)

#### 使用容积 Use volume (D×H mm)

#### 网篮尺寸 (上长×上宽×下长×下宽×高mm) Basket size(UpL\*Upw\*DownL\*DownW\*Hmm)

#### 时间设定范围 Time setting range

#### 额定工作压力 Rated working pressure

#### 温度设定范围 TEMP setting range

### WDZX-200KC

智能半自动控制  
Semi-auto

不锈钢 Stainless steel

3.0 (参考 Reference)

300kg

380V/9kW

1640×830×1800

1550×720×1640

500×1120

480×440×480×250×190

1~5999 min

0.217MPa

50~134℃

### WDZX-300KC

智能半自动控制  
Semi-auto

不锈钢 Stainless steel

3.0 (参考 Reference)

335kg

380V/10.5kW

1640×930×1900

1550×820×1740

600×1240

500×540×500×300×230

1~5999 min

0.217MPa

50~134℃